



FA 20 100 XX

P. 1 | 2



HS CODE
56090090
CARTON SIZE / PCS.
FA 20 100 10 : 80 x 40 x 24 cm / 10 FA 20 100 20 : 80 x 40 x 24 cm / 5 FA 20 100 30 : 80 x 40 x 24 cm / 5 FA 20 100 40 : 80 x 40 x 24 cm / 3 FA 20 100 50 : 80 x 40 x 24 cm / 3
AET N°2777/10357-02/E03-01
Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
MODULE D FI14/14003.02
SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland
AET (UKCA) N°AB0321/16014-01/E01-01
Satra Technology Centre, N°0321 Wyndham Way, Telford Way, Kettering Northamptonshire, NN16 8SD, United Kingdom
MODULE D 11 IN14/14003
SGS United Kingdom Ltd., N°0120 Unit 202B, Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom



REF.	FA 20 100 XX
	10m 20 m 30 m 40 m 50 m MAX. 100 KG
	EN 353-2:2002
MAT.	Polyamide Ø 14 – 16 mm
	---
	---
R(kN)	15 kN
+	FA 20 100 00A / FA 20 100 00B
	1.25 kg 2.50 kg 3.90 kg 5.15 kg 6.05 kg



Longueur Poids maxi utilisateur
Length Max. user weight
Longitud Peso máximo del usuario
Lunghezza Peso Max. dell'utente
Länge Höchstgewicht des Benutzers



Matière connecteur
Material of connector
Material conector
Materiale connettore
Material des Verbinders



Coulisseau doté d'un point fixe
Rope grab with a fixed point lock
Corredera provista de punto fijo
Guida a punto fisso
Gleitelement mit Festpunkt

+

À utiliser avec
To be used with
Para usar con
Ad essere utilizzato con
Verwendet werden soll mit