



FA 30 702 20



FA 30 703 20



HS CODE
56090090
CARTON SIZE / PCS.
FA 30 702 20 : 40 x 40 x 24 / 12
FA 30 703 20 : 60 x 40 x 24 / 12
AET N°2777/10965-01/E01-01
Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
MODULE D FI14/14003.02
SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland
AET (UKCA) N°AB0321/16020-01/E01-01
Satra Technology Centre, N°0321 Wyndham Way, Telford Way, Kettering Northamptonshire, NN16 8SD, United Kingdom
MODULE D 11 IN14/14003
SGS United Kingdom Ltd., N°0120 Unit 202B, Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom

REF.	FA 30 702 20	FA 30 703 20
LG.  KG	1.4 m / 1.8 m (connector included)	1.4 m / 2 m (connector included)

	Max. 100 KG	
CE	EN 355:2002	
MAT.	 45 mm  PES	
	35 mm	45 mm
	 --- / FA 50 207 55 FA 50 202 17 / FA 50 207 55	
	NO	
+	---	
	0.87 KG	1.14 KG



Largeur de l'absorbeur d'énergie
Width of the energy absorber

Ancho del absorbedor de energía
Larghezza del assorbitore di energia

Breite des Falldämpfers

LG.



Longueur Poids maxi utilisateur
Length Max. user weight

Longitud Peso máximo del usuario

Lunghezza Peso Max. dell'utente

Länge Höchstgewicht des Benutzers



Matière connecteur haut / connecteur bas
Material of top connector / bottom connector

Material conector alto / conector bajo
Materiale connettore alto / connettore basso
Material oberes / unteres Verbindungselement



Ouverture
Gate opening

Apertura
Apertura
Öffnung



Homologué pour le travail à proximité d'arêtes vives
Approved for work near sharp edges

Homologado para trabajo cerca de aristas vivas

Omologato per lavoro in prossimità di spigoli vivi

Zugelassen für Arbeiten in der Nähe scharfer Kanten