






FA 40 600 10, FA 40 600 15



REF.	FA 40 600 XX
CE	EN 354:2010
LG.	1.0 m 1.5 m
MAT.	 PA 11 mm Polyamide
	STEEL
R (kN)	22 kN
Kg	1.45 KG 1.53 KG

MAT.		R (kN)
Matière	Matière connecteurs	Résistance (en kN)
Material	Material of connectors	Resistance (kN)
Material	Material de los conectores	Resistencia (en kN)
Materia	Materie connettori	Resistenza (in kN)
Material	Material der Verbinder	Belastbarkeit (in kN)

HS CODE	63079098
CARTON SIZE / PCS.	60 x 40 x 24 cm / 12
AET (UE) N°2777/10360-02/E05-01	Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
MODULE D F14/14003.02	SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland
AET (UKCA) N°AB0321/16027-01/E01-01	Satra Technology Centre, N°0321 Wyndham Way, Telford Way, Kettering Northamptonshire, NN16 8SD, United Kingdom
MODULE D 11 IN14/14003	SGS United Kingdom Ltd., N°0120 Unit 202B, Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom