





FA 60 0006 10/20:

PVC +  STEEL

FA 60 006 10S/20S:

 NOX

<b>HS CODE</b>
76169990
<b>CARTON SIZE / PCS.</b>
<b>FA 60 006 10/S : 40 x 40 x 24 cm / 25</b>
<b>FA 60 006 20/S : 40 x 40 x 24 cm / 20</b>
FA 60 006 XX: AET (UE) N°2777/10790-01/E01-01
FA 60 006 XXS: AET (UE) N°2777/10792-02/E01-02
<b>Satra Technology Europe Ltd., N° 2777,</b> Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
<b>MODULE D FI14/14003.02</b>
<b>SGS Fimko Oy, N°0598</b> Takomotie 8, 00380 HELSINKI, Finland

REF.	FA 60 006 10   FA 60 006 20	FA 60 006 10S   FA 60 006 20S
CE	EN 795:2012 Type B	EN 795:2012 Type B, EN 354:2010
	x1	
LG.	1.0 m   2.0 m	1.0 m   2.0 m
MAT.	PVC /  STEEL Ø 8.0 mm	 INOX Ø 8.0 mm
R (kN) / MBS (kN)	12 kN / 25 kN	
	0.56 kg   0.80 kg	0.46 kg   0.74 kg



**Nombre d'utilisateurs**  
 Number of users  
**Cantidad de usuarios**  
 Quantità di utilizzatori  
**Anzahl der Benutzer**

**R (kN) / MBS (kN)**

**Résistance statique (en kN) / Résistance à la rupture**  
 Static strength / Minimum Breaking Strength  
**Resistencia estática (en kN) / Resistencia a la ruptura (en kN)**  
 Resistenza statica (in kN) / Resistenza alla rottura (in kN)  
**Statische Festigkeit (in kN) / Bruchfestigkeit (in kN)**